ISO-TEX 205

TECHNICAL DATA SHEET

GRANULE

ACRYLIC LATEX

DESCRIPTION

ISO-TEX 205 series is a decorative textured coating based on Acrylic Latex and granules from volcanic rocks.

USE

ISO-TEX can be used indoors and on exterior foundations only (subject to certain conditions; see Limitations).
It is suitable for residential, commercial, or institutional projects.

ADVANTAGES

- Its strong consistency makes it possible to fill the cavities of irregular surfaces.
- When dry, it gives a rich, grainy finish.
- Rustic appearance
- Ecological
- This coating contains a low level of VOCs

LIMITATIONS

- Avoid application at temperatures below 10°C or in direct sunlight.
- Do not apply on the floor.
- Must be topcoated for applications on exterior foundations (see Recommended finish)

TECHNICAL DATA

Resin		Acrylic Latex and granule	
Color		White	
Solvent		Water	
Flash Point		N/A	
Inflammability		N/A	
Solids by weight		73	%
Solids by volume		58	%
VOC		<50	g/l
Gloss	60°	N/A	%
Sheen	85°	N/A	%
Standards	Type 1GP 162		

APPLICATION DATA

*At 25° Celsius
Relative humidity at 50%
May differ depending on the colour

Spreading Rate May vary depending on the surface porosity		4,8-9,6 m^2 (500-100sqft)	gallon
Film Thickness	Wet	16-32	mils
	Dry	9,3-18,6	mils
Drying Time*	Tack free	2	hour
	Recoat	4	hours
Application	Trowel	√	
	Roller	Textured	
	Spray Airless	N/A	lb/sqin
Exterior application and condition		N/A	
Storage	Temperature between	10 et 30	°C

	Format		
Base	946ML	3,78L	18,9L
205-0 White		√	√

ISO-TEX

GRANULE

205

ACRYLIC LATEX

SURFACE PREPARATION

The surface must be dry and clean, free of dust, oil, grease, rust, and soap. On a previously painted surface, it is recommended to wash with a degreaser (TSP) to remove any contaminants that may affect the adhesion and hardening of the product. Shiny surfaces MUST be well sanded and dusted.

RECOMMENDED PRIMERS

Drywall or interior masonry: Apply Latex Plus 170 primer sealer.
Exterior masonry: Apply 270 undercoat before applying ISO-TEX.
Latex paint: No primer required**.**
Interior Glossy alkyd paint: Apply Adhéro Plus 290 undercoats**.**

RECOMMEND FINISH

If applied outside, the ISO-TEX must be top coated with 2 coats of Atmosphere exterior paint 2268 matte or 2260 Satin. For interior application no restriction is needed.

APPLICATION

Mix well before use. Apply evenly using a trowel and a textured roller and be sure to always complete the last strokes of the roller in the same direction. Even out the texture perfectly, if necessary, by re-rolling the already covered and undried surface without adding ISO-TEX.

WARRANTY

This product will give complete satisfaction if applied according to the manufacturer's instructions. In the event that this is found to be defective after inspection, the manufacturer's liability is limited to replacement of the product and does not include labor during application.

CAUTION

- Keep out of the reach of children
- Keep container closed when not in use
- Avoid freezing

CONTACT YOUR MUNICIPALITY TO DISPOSE OF THE CONTAINER IN AN ENVIRONMENTALLY-FRIENDLY MANNER.