PRODUCT INFORMATION
MAINTENANCE OIL

IDEAL FOR REFRESHING AND MAINTAINING POLYX®-OIL SURFACES.



3079 Clear Matt | 3081 Clear Satin | 3098 Clear Semi-matt (R9) | 3440 White transparent Satin | 3059 Black Matt (R9)





PRODUCT DESCRIPTION:

Osmo Maintenance Oil is for the basic and routine maintenance of oiled and waxed wooden flooring. Dull and matt flooring is refreshed with Osmo Maintenance Oil. By applying Maintenance Oil at the right time, time-consuming sanding works and renovation can be avoided. Also suitable for changing the sheen. Suitable for wood; microporous surface will not crack, peel, flake or blister. Resistant to wine, beer, cola, coffee, tea, fruit juice, milk and water in accordance with German DIN 68861-1A/ EN 12720 – no water spots. The dry coating is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3). The dried coating fulfils the fire rating B2 (normal flammability) according to German DIN 4102.

RECOMMENDED USE:

For the maintenance and care of all wooden flooring treated with Polyx®-Oil: solid wood, plank, parquet, strip, OSB and cork flooring, as well as stairs and furniture surfaces. Highly recommended for public interiors (e.g. restaurants, museums and other high traffic floors).

INGREDIENTS:

Binding agent based on natural plant oils (sunflower oil, soybean oil, thistle oil) and waxes, paraffin, titanium dioxide white pigment, siccatives (drying agents) and water-repellent additives. Dearomatised white spirit (benzene-free). Detailed declaration of ingredients available upon request.

TECHNICAL DATA:

Specific weight: 0.900-0.930 g/cm³ (DIN ISO 2811-2)
Viscosity: 35-55s (DIN 53211/3mm)
Odour: faint/mild, odourless after drying
Flashpoint: >60°C (DIN EN ISO 2719)

STORAGE:

5 years or longer if stored in the originally closed container. If thickened by frost, store at room temperature for 24 hours prior to use.

SURFACE PREPARATION:

The oiled wood surface must be clean, dry and free of dust. Clean wooden flooring thoroughly with Osmo Intensive Cleaner and wipe the surface with clear water. Clean furniture and stair surfaces with Osmo Spray Cleaner and wipe the surface with clear water.

The finished surface and the product coverage are influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

METHODS OF APPLICATION:

Osmo Maintenance Oil is ready to use. Before use shake well, or stir larger containers (2.5 L) well. Apply thinly with Osmo Floor Brush, Flat Brush, a trowel or Osmo Microfibre Roller, and buff in with Osmo FloorXcenter or HandXcenter and a white pad. Remove excess product. For smaller areas, Osmo Maintenance Oil can be applied with a lint-free cloth. Ventilate well while drying.

Osmo Holz und Color GmbH & Co. KG | Affhüppen Esch 12, D-48231 Warendorf | Postfach 110161 | D-48203 Warendorf
Telefon +49 (0) 25 81 / 9 22-100 | Telefax +49 (0) 25 81 / 9 22-200 | info@osmo.de | **www.osmo.com**

PRODUCT INFORMATION
MAINTENANCE OIL

CLEANING OF TOOLS:
With Osmo Brush Cleaner (free of aromatic compounds).

DRYING TIME:
Approx. 3-5 hours (normal climatic conditions, 20-23°C/ 50-65% rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times significantly.

COVERAGE:
Product coverage for 1 coat is 40-60 m²/1 l. It depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

RECOMMENDATION:
Ready to use - do not thin! Apply thinly and evenly to the clean wood surface with Osmo Flat Brush, Finish Applicator Fleece, Floor Brush or Microfibre Roller along the wood grain and buff in evenly with Osmo HandXcenter or FloorXcenter and a white pad (approx. 15-20 ml/m²). A trial application should always be carried out - especially on unknown substrates! If necessary, clean flooring with Intensive Cleaner prior to care treatment. Clean furniture and stair surfaces beforehand with Osmo Spray Cleaner.

NOTE:
Maintenance Oil 3098 semi-matt (R9) must not be buffed in with a single-disc machine. For a slip-resistant surface, apply the Maintenance Oil thinly using only with an Osmo Microfibre Roller. If the wood is raw or has already greyed, the surface must be sanded and treated with an Osmo Polyx®-Oil.

CAUTION:
Keep out of reach of children. Safety data sheet available on request. Warning: Materials impregnated with liquid product, such as cloths, may self-ignite. After use, let the materials to dry completely either spread out flat or in a closed metal container and then dispose of them properly. EU VOC limit value for this product: out of scope.

DISPOSAL:
Dispose of product residues according to the official guidelines (European Waste Code (EWC)-Code 08 01 12). Only completely emptied cans can be recycled.

COLOUR TONE:
3079 Clear Matt
3081 Clear Satin
3098 Clear Semi-matt (R9)
3440 White transparent Satin
3059 Black Matt (R9)

SIZE:
1.0 l; 2.5 l

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. Upon publication of a new version of this product information, the new information shall replace any previous product information.
For information specific to a certain country or region, please consult your local wholesaler or dealer:
OSMO UK,
Smeaton Close
Unit 24 Anglo Business Park
Aylesbury, Bucks HP19 8UP
Phone: 01296 481 220, www.osmouk.com

Version 09/26