PRODUCT INFORMATION
WOOD REVIVER POWER-GEL

HIGHLY EFFECTIVE CLEANING AND REFRESHING OF GREYED WOOD!



6609 Clear

PRODUCT DESCRIPTION:

Cleaner for refreshing and cleaning greyed wood in outdoor areas. Wood Reviver Power-Gel is a non-drip product, and thus it is easy to apply – especially on vertical surfaces. The gel penetrates the wood deeply and removes grey patina, and afterwards by re-oiling, the fresh warm colour tone of the wood is restored.

RECOMMENDED USE:

Osmo Wood Reviver Power-Gel is highly recommended for timber decking, cladding, garden furniture and similar surfaces.

INGREDIENTS:

Osmo Wood Reviver Power-Gel contains biodegradable oxalic acid (< 5 %) and preservatives (C(M)IT/MIT). This product is free of solvents, formaldehyde, chlorine compounds and amines.

TECHNICAL DATA:

Specific weight: 0.99-1.05 g/cm³ (DIN ISO 2811-2)
Viscosity: 6500-10000 mPas
Odour: faint/mild, odourless after drying
Flashpoint: not required
pH value: >2.1

STORAGE:

2 years or longer if stored in the originally closed container. Do not expose to frost or temperatures above 30 °C!

SURFACE PREPARATION:

Remove debris from greyed wood; afterwards dampen with water. Wood Reviver Power-Gel is ready to use. Do not thin. Perform a trial application before treating wood with Wood Reviver Power-Gel.

METHODS OF APPLICATION:

Generously apply the gel along the wood grain. After approx. 20 minutes reaction time, clean surface with Osmo Decking Cleaning Brush and rinse with a lot of water. After drying for approx. 48 hours, protect the newly refreshed wood with a wood finish (e.g. Osmo Exterior Oil Woodstain, Decking-Oil, Country Colour). For machine processing on decking, we recommend using Osmo Decking and Flooring Cleaner.

CLEANING OF TOOLS:

With soap and water.

DRYING TIME:

Before applying a new coating, allow the wood to dry thoroughly (approx. 24-48 hours) under normal climatic conditions (20-23°C/50-65% rel. humidity). Lower temperatures and/or higher air humidity may increase drying times significantly.

COVERAGE:

1 litre treats approx. 10 m² (depending on level of greying) with one application. Coverage depends significantly on the condition of the wood. All information refers to

Osmo Holz und Color GmbH & Co. KG | Affhüppen Esch 12, D-48231 Warendorf | Postfach 110161 | D-48203 Warendorf
Telefon +49 (0) 25 81 / 9 22-100 | Telefax +49 (0) 25 81 / 9 22-200 | info@osmo.de | **www.osmo.com**

PRODUCT INFORMATION
WOOD REVIVER POWER-GEL

smooth and planed/ sanded surfaces. Other surfaces may lead to differences in coverage.

NOTE:

Protect metal (e.g. hinges), sensitive mineral surfaces (e.g. marble) and plants against direct contact (e.g. cover ornamental and farm plants with a tarpaulin.) Do not release into decorative and fishponds, if possible!

CAUTION:

Causes serious eye damage. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Wear eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor. Contains Oxalic acid ; mixture of CIT and MIT (3:1) (preservatives). May produce an allergic reaction.

Always follow the information on the product label. Note: Protect metal (e.g. hinges) and plants against direct contact (e.g. cover ornamental and farm plants with a tarpaulin.)



Danger

DISPOSAL:

Dispose of product residuals according to the official guidelines (European Waste Code (EWC)-Code 20 01 30). Only completely emptied cans can be recycled.

COLOUR TONE:

6609 Clear

SIZE:

0.5 l; 2.5 l; 5.0 l; 10 l

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. Upon publication of a new version of this product information, the new information shall replace any previous product information.
For information specific to a certain country or region, please consult your local wholesaler or dealer:
OSMO UK,
Smeaton Close
Unit 24 Anglo Business Park
Aylesbury, Bucks HP19 8UP
Phone: 01296 481 220, www.osmouk.com

Version 09/26